



US009410356B2

(12) **United States Patent**
Yuhas

(10) **Patent No.:** **US 9,410,356 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **CURVED DOOR**

(71) Applicant: **AS IP HOLDCO, LLC**, Piscataway, NJ (US)

(72) Inventor: **Drew Yuhas**, Pennington, NJ (US)

(73) Assignee: **AS IP HOLDCO, LLC**, Piscataway, NJ (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/931,577**

(22) Filed: **Jun. 28, 2013**

(65) **Prior Publication Data**

US 2015/0000196 A1 Jan. 1, 2015

(51) **Int. Cl.**
E06B 3/46 (2006.01)
E06B 3/70 (2006.01)
A47K 3/34 (2006.01)

(52) **U.S. Cl.**
CPC **E06B 3/4636** (2013.01); **A47K 3/34** (2013.01); **E06B 3/7007** (2013.01)

(58) **Field of Classification Search**
CPC A47K 3/34; E06B 3/4636
USPC 49/38, 39, 40, 41, 61, 63, 409, 410, 49/411, 125; 4/607, 610
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,997,420 A * 4/1935 Kiekert 49/125
2,028,628 A * 1/1936 Sherron 49/40
3,052,930 A * 9/1962 Mathews 49/411
3,350,739 A * 11/1967 Rifkin 16/90
D217,866 S 6/1970 Myers

4,114,331 A * 9/1978 Yamamoto 52/202
4,178,718 A * 12/1979 Laby 49/411
4,545,630 A * 10/1985 Izumi G01D 11/24 177/238
4,807,312 A 2/1989 Baus
4,882,795 A * 11/1989 Baus 4/607
4,974,269 A 12/1990 Baus
D352,548 S 11/1994 Pinsky et al.
D374,917 S 10/1996 Casden
5,575,022 A * 11/1996 Duffy et al. 4/607
D392,724 S 3/1998 Lenardon
5,839,228 A * 11/1998 Duffy 49/223
5,852,837 A * 12/1998 Hustung 4/607
5,987,817 A * 11/1999 Hein 49/40
6,023,889 A 2/2000 Hustung et al.

(Continued)

FOREIGN PATENT DOCUMENTS

DE 4125069 3/1992

OTHER PUBLICATIONS

MTI Baths, Enclosures—Shower Enclosures—Crescent Bow-Front Enclosure—N60BF, <http://mtibaths.com/products/enclosures/shower/N60BF>, retrieved on Mar. 11, 2013.

(Continued)

Primary Examiner — Gregory Strimbu

(74) *Attorney, Agent, or Firm* — Ladas & Parry LLP

(57) **ABSTRACT**

A curved bypass door suitable for a shower or bath comprising a first door, a second door set back from the first door, and an upper track made of aluminum. In one aspect, the upper track has a lower rail adapted to receive a first roller for the first door and an upper rail adapted to receive a second roller for the second door. In another aspect, the upper rail is adapted to receive the roller of the second door and the lower rail is adapted to receive and fixedly hold the first door. Each door curvature such that both doors together form the curved bypass door. The upper track is curved to match the shape of the curved bypass door.

15 Claims, 23 Drawing Sheets

